



To be setup in accordance with TA 20 of the MUTCD

Table I Device Spacing				
Speed (mph)	Max. Distance Between Devices (ft)			
	Cones or Tubular Markers		Type I or Type II Barrieroles or Vertical Panels or Drums	
	Taper	Tangent	Taper	Tangent
25	25	50	25	50
30 to 45	25	50	30	50
50 to 70	25	50	50	100

**ASTSA**
AMERICAN TRAFFIC SAFETY
SERVICES ASSOCIATION

This is to affirm that
Mark Meyers
has satisfactorily completed the
**Florida Advanced Work Zone
Traffic Control Course**
Date Complete: 05/24/2011 Status: PASS
Location: Fort Lauderdale Instructor: Ms. Catherine Witt
Date Refresher Course Required: 05/24/2015

ID #37

DISTANCE BETWEEN SIGNS			
Speed	Spacing (ft)		
	A	B	C
40 mph or less	200	200	200
45 mph	350	350	350
50 mph	500	500	500
*55 mph or greater	2640	1640	1000

- * The ROAD WORK 1 MILE sign may be used as an alternate to the ROAD WORK AHEAD sign and the RIGHT LANE CLOSED 1/2 MI sign may be used as an alternate to the RIGHT LANE CLOSED AHEAD sign.
CAM 16-0166 Exhibit 2b
- * 500' beyond the ROAD WORK AHEAD sign or midway between signs whichever is less. **Page 1 of 1**