

FIVEASH WATER TREATMENT PLANT EVALUATION UPDATE

February 4, 2020



CAM 20-0117 Exhibit 2 Page 1 of 11

Project Scope

CAM 20-0117 Exhibit 2 Page 2 of 11

Project Scope

• Existing Facility Condition Assessment

• Existing Water Resources Evaluation

Treatment Systems Investigation






Page 3 of 11


Project Findings

CAM 20-0117 Exhibit 2 Page 4 of 11

Existing Facility Condition Assessment

- Performed evaluation & visual inspection of existing facilities (Treatment Plant & Wellfield)
- Visual Condition Assessment





/ tuu omenoli

Existing Facility Condition Assessment

Conclusions:

- Facility has reached/exceeded projected life
- Findings consistent with the findings of the 2017
 Comprehensive Utility Strategic Master Plan

Recommendations

- Limit investment to that necessary for current operations
- Do not invest in facility to meet identified goals (water quality, reliability, resiliency, etc.)

Original construction – 1954 (66 years ago) Type Time (in years) Wells 20-30 Water Treatment Plant Structures 32 Water Treatment Equipment 22 **Miscellaneous Equipment** 25 Storage Reservoirs 40 **Transmission & Distribution Mains** 43 From FAC 25-30.115 and 25-30.140

Existing Water Resources Evaluation

- Assessed planning period needs (2035) 50 million gallons per day
- Evaluated existing SFWMD water use permit (WUP) allocations
- Performed comparison of C-51 source with Floridan Aquifer source

Conclusions

- Existing WUP allocations are sufficient for planning period needs
- Purchase/utilization of C-51 water is cost effective for post planning period requirements
 - 3 mgd reserved
 - Additional 3 mgd planned



Treatment Systems Investigation

 Investigated Multiple Treatment Process Combinations

- Replacement facility location evaluation
 - Fiveash Site
 - Prospect Wellfield

Performed siting and cost analysis





Treatment Investigation

18 Treatment Systems Investigated

Primary Goals:

- Meet all regulatory requirements
- Achieve enhanced/improved aesthetic objectives (color, taste/odor, etc.)
- Establish "state of the art"/robust treatment system for the long term
- Optimize fiscal and operational considerations
- Plan for future considerations (future regulations, byproducts disposal, etc.)

Parameter	Units	Goal	Fiveash Effluent Water Quality (2014)	Peele-Dixie Effluent Water Quality (2014)	Primary Drinking Water Standards	Secondary Drinking Wate Standards
Total Hardness	mg/L as CaCO3	50 - 120	77.3	17.4	NS	NS
Sodium	mg/L	< 50	36.5	<50	160	NS
Total Dissolved Solids (TDS)	mg/L	< 500	<500	<500	NS	500
Iron	mg/L	< 0.3	0.02	0.10	NS	0.3
Manganese	mg/L	< 0.05	ND	<0.05	NS	0.05
Fluoride	mg/L	< 0.7	0.58	0.6	4.0	2.0
Sulfate	mg/L	< 200	ND	<200	NS	250
Chloride	mg/L	<100	66.5	16.7	NS	250
Color	Pt-Co	< 8	15.2	1.9	NS	15
Turbidity	NTU	< 1	0.16	0.16	NS	NS
Alkalinity	mg/L as CaCO3	> 40	60.7	54.1	NS	NS
H2S	mg/L	< 0.1	<0.1	<0.1	NS	NS
pН	Units	8.0 - 8.5*	9.19	9.0	NS	6.5-8.5
TTHM	mg/L	< 0.06	0.064	0.064	0.08	NS
HAA ₅	mg/L	< 0.04	0.0318	0.0318	0.06	NS
Free Ammonia	mg/L	<0.2	<0.5	<0.5	NS	NS
Corrosivity		Non Corrosive	Non Corrosive	Non Corrosive	NS	Non Corrosiv
LSI	units	> 0.2	>0.3	0.3	NS	NS



Treatment Systems Investigation

- Conclusions
 - Granular Activated Carbon (GAC) & Seawater Desalination
 more expensive than other options
 - Multiple treatment schemes available to achieve goals
 - Prospect Wellfield site is most suitable for replacement facility
 - Most "state of the art"/robust treatment system would consist of nanofiltration and ion exchange system
 - Conceptual capital cost range \$350 -\$400+ million



CAM 20-0117 Exhibit 2 Page 10 of 11

Questions?



CAM 20-0117 Exhibit 2 Page 11 of 11